

A white Otokar Ural 4x4 light armored tactical vehicle is shown in a desert environment. The vehicle features a high roof with multiple windows, a front grille with a metal mesh, and large, rugged tires. It is parked on sandy ground with hills in the background under a clear blue sky.

**4x4 LIGHT
ARMORED TACTICAL VEHICLE**

URAL

Otokar

URAL



URAL Tactical Wheeled Armored Vehicle family is designed for flexibility, with a modular structure and adaptable design, making it suitable for a variety of missions. Two different power packs and various mission equipment are available. This vehicle is highly adapted to different roles and missions, offering superior protection and mobility.

Double Cab
Armored
Personnel Carrier



Armored Personnel
Carrier 7.62 mm
One Manned Turret



Armored
Personnel Carrier



Special Operations
Vehicle



Tactical Ladder
Vehicle



Armored
Personnel Carrier
RCWS



7.62 mm
Open Cupola Armored
Personnel Carrier



Armored Internal
Security Vehicle



Armored
Ambulance



URAL TECHNICAL SPECIFICATIONS

WEIGHT AND DIMENSIONS

Gross Vehicle Weight
Personnel Capacity
Overall Length
Overall Width
Overall Height
Ground Clearance (Under belly)

ENGINE

GEARBOX

TRANSFER BOX

FRONT / REAR AXLES

SUSPENSION

BRAKES

STEERING

TYRES

ELECTRICAL SYSTEM

STANDARD URAL 168 HP

6400 kg
8, including the driver and commander
4900 mm (excluding winch and spare wheel)
2200 mm (excluding mirrors)
2440 mm (top of roof)
320 mm

Turbo Charged Diesel Engine, 168 HP
Automatic, 6 speed forward, 1 speed reverse
Permanent four-wheel drive,
2-Speed incorporating centre differential

Independent front suspension,
rigid rear axle

Chassis mounted independent suspension,
anti-roll bar with torsion bar and telescopic-
hydraulic shock absorbers at the front. Chassis
mounted rigid axle with parabolic leaf spring and
telescopic-hydraulic shock absorbers at the rear
Air-over-hydraulic, dual line brake system
Hydraulically assisted, forward-backward
and up-down adjustable steering wheel
Left-hand drive or right-hand drive
Military type run-flat tyres

24 Volts electrical system installation,
10 Amperes alternator, 2x12 Volts 105 Ah batteries

OPTION URAL 250 HP


8000 kg
8, including the driver and commander
4900 mm (excluding winch and spare wheel)
2200 mm (excluding mirrors)
2480 mm (top of roof)
350 mm

Turbo Charged Diesel Engine, 250 HP
Automatic, 6 speed forward, 1 speed reverse
Permanent four-wheel drive,
2-speed incorporating centre differential

Chassis mounted all independent axles on
front and rear

Chassis mounted all independent suspension
axles, anti-roll bar with coil springs and
telescopic-hydraulic shock absorbers at the
front and rear

Air-over-hydraulic, dual line brake system with ABS
Hydraulically assisted, forward-backward and
up-down adjustable steering wheel
Left-hand drive or right-hand drive
Military type run-flat and 325/85 R16 tyres
24 Volts electrical system installation,
120 Amperes alternator, 2X12 Volts 105 Ah batteries



All text and illustrations shown in this brochure are not binding and are provided for guidance only. OTOKAR reserves the right to introduce modifications in line with technical progress and change the product specifications without any prior notice.



Otokar

Otokar Otomotiv ve
Savunma Sanayi A.Ş.

Head Office:

Taşdelen Mahallesi,
Sırn Çelik Bulvarı No:5 Çekmeköy
34788 İstanbul, Türkiye
T: +90 216 489 29 50
F: +90 216 489 29 67

Factory:

Atatürk Caddesi No: 6
Arifiye 54580 Sakarya, Türkiye
T: +90 264 229 22 44
F: +90 264 229 22 42

www.otokar.com.tr/en